## Samsung Q Q1 Ultra HSDPA Intel® Pentium® 40 GB 17.8 cm (7") 1 GB Black

Brand : Samsung

Product family: Q

Product code: NP-Q1U/AUT/SEI

Product name : Q1 Ultra HSDPA

Samsung Q Q1 Ultra HSDPA. Display diagonal: 17.8 cm (7"), Display resolution: 1024 x 600 pixels. Internal storage capacity: 40 GB. Processor frequency: 0.8 GHz, Processor family: Intel® Pentium®. Internal memory: 1 GB. Card reader integrated. Weight: 690 g. Product colour: Black





## Display Design 17.8 cm (7") Form factor \* Slate Display diagonal \* Display resolution \* 1024 x 600 pixels Product colour \* Black Processor Performance Processor family \* Intel® Pentium® GPS (satellite) × Processor frequency \* 0.8 GHz Position location \* × Processor front side bus 400 MHz Battery Memory Battery technology \* Lithium-Ion (Li-Ion) Internal memory \* 1 GB Number of battery cells 4 Maximum internal memory 1 GB Power Memory clock speed 667 MHz AC adapter power 60 W Storage 100 - 240 V AC adapter input voltage Internal storage capacity \* 40 GB 50 - 60 Hz AC adapter frequency Card reader integrated \* 1 AC adapter output voltage 19 V Graphics Weight & dimensions Maximum graphics card memory 128 MB Width 227.5 mm Depth 123.9 mm Audio Height 22.9 mm Built-in microphone 1 Weight 690 g 2 Number of built-in speakers **Operational conditions** Camera Operating temperature (T-T) 10 - 32 °C Built-in camera 1 -5 - 40 °C Storage temperature (T-T) Main camera resolution (numeric) 1.3 MP Operating relative humidity (H-H) 20 - 80% Network 5 - 90% Storage relative humidity (H-H) Bluetooth 1 Other features Bluetooth version 2.0+EDR Internal modem × Ports & interfaces Networking features Fast Ethernet, WLAN USB 2.0 ports quantity 2 Infrared data port × Ethernet LAN (RJ-45) ports 1 VGA (D-Sub) ports quantity 1

| Ports & interfaces |   | Other features     |                     |
|--------------------|---|--------------------|---------------------|
| Microphone in      | 1 | Memory slots       | 1 x SODIMM          |
| Headphone out      | 1 | Cabling technology | 10Base-T/100Base-TX |
| DC-in jack         | ✓ | Docking connector  | ×                   |

**Catalog Object Cloud** 



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.