

## HP 6005 Pro MT AMD Athlon X2 B22 2 GB DDR3-SDRAM 250 GB AMD Radeon HD 4200 Windows Vista Business Micro Tower PC

Brand : HP Product code: VN791ET\_RA374AT

Product name: 6005 Pro MT

6005 Pro MT AMD Athlon II X2 B22 2.8GHz, 2 x 1 GB DDR3 SDRAM, 250GB SATA, SATA DVD+/-RW 16x SuperMulti LightScribe, ATI Radeon HD 4200, HP Media Card Reader, Windows XP Professional / Windows® Vista Business & LP1965 19" LCD, 1000:1, 300 cd/m2, 6 ms
HP 6005 Pro MT. Processor frequency: 2.8 GHz, Processor family: AMD Athlon X2, Processor model: B22. Internal memory: 2 GB, Internal memory type: DDR3-SDRAM, Memory clock speed: 1333 MHz. Total storage capacity: 250 GB, Card reader integrated, Optical drive type: DVD Super Multi. Discrete graphics card model: AMD Radeon HD 4200. Operating system installed: Windows Vista Business. Chassis type: Micro Tower. Product type: PC. Weight: 9.3 kg





Processor		Performance	
Processor manufacturer * AMD Processor family * AMD Athlon : Processor model * B22 Processor frequency * 2.8 GHz Processor cache 2 MB Processor cache type L2	AMD Athlon X2	Motherboard chipset Audio system Product type *	AMD 785G HDA PC
	2 MB	Software Operating system installed *	Windows Vista Business
Memory		Power Power consumption (typical)	320 W
Internal memory * Maximum internal memory *	2 GB 8 GB	Operational conditions	
Internal memory type Memory layout (slots x size) Memory clock speed	DDR3-SDRAM 2 x 1 GB 1333 MHz	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	10 - 35 °C -30 - 60 °C 10 - 90%
Storage		Storage relative humidity (H-H)	5 - 95%
Total storage capacity * Optical drive type * HDD interface HDD speed Card reader integrated	250 GB DVD Super Multi SATA 7200 RPM	Weight & dimensions  Width *  Depth *  Height *  Weight *	176 mm 430 mm 377 mm 9.3 kg
Graphics		Display	
On-board graphics card * Discrete graphics card model * Maximum graphics card memory	✓ AMD Radeon HD 4200 0.5 GB	Display included * Display diagonal Display resolution	48.3 cm (19") 1280 x 1024 pixels
Ports & interfaces USB 2.0 ports quantity * VGA (D-Sub) ports quantity	10 1	Contrast ratio (typical) Display brightness Viewing angle, horizontal Viewing angle, vertical	1000:1 300 cd/m <sup>2</sup> 178° 178°

Ports & interfaces		Other features	
PS/2 ports quantity Ethernet LAN (RJ-45) ports Microphone in Headphone outputs Serial ports quantity	2 1 ✓ 1	Power requirements Video adapter, bus Storage drive controller LightScribe Display	100 - 240 VAC, 50/60 Hz PCI Express x16 SATA 3.5Gb/s NCQ SMART IV  ✓ LCD
Expansion slots PCI Express x1 slots PCI Express x16 slots	2 1	Expansion slots Networking features Graphics card family	1 x PCI Gigabit Ethernet AMD
Design Chassis type * Country of origin	Micro Tower China		

