
ASUS Chromebook Flip C213NA-BU0058-BR Intel® Celeron® N3350 29,5 cm (11.6") Touchscreen HD+ 4 GB LPDDR4-SDRAM 32 GB eMMC Wi-Fi 5 (802.11ac) ChromeOS Grey

Brand: ASUS **Product family:** Chromebook Product code: 90NX01C1-

M00690



BU0058-BR



ASUS Chromebook Flip C213NA-BU0058-BR. Product type: Chromebook, Form factor: Convertible (Folder). Processor family: Intel® Celeron®, Processor model: N3350, Processor frequency: 1,1 GHz. Display diagonal: 29,5 cm (11.6"), HD type: HD+, Display resolution: 1600 x 900 pixels, Touchscreen. Internal memory: 4 GB, Internal memory type: LPDDR4-SDRAM. Total storage capacity: 32 GB, Storage media: eMMC. Operating system installed: ChromeOS. Product colour: Grey



Design		Processor special features	
Product type * Product colour *	Chromebook Grey	book Intel® Wireless Display (Intel® WiDi)	
Form factor *	Convertible (Folder)	Intel Smart Connect Technology	X
Display		Intel® Anti-Theft Technology (Intel® AT)	×
Display diagonal *	29,5 cm (11.6")	intel® Smart Response reciniology	x
Display resolution * Touchscreen *	1600 x 900 pixels ✓	Intel® Identity Protection Technology (Intel® IPT)	•
HD type Touch technology	HD+ Multi-touch	Intel® Hyper Threading Technology (Intel® HT Technology)	×
LED backlight	✓	Intel® Turbo Boost Technology	X
Native aspect ratio	16:9	Intel® Small Business Advantage (Intel® SBA)	×
Processor	Lited	Intel® High Definition Audio (Intel® HD Audio)	✓
Processor manufacturer * Processor family *	Intel Intel® Celeron®	Enhanced Intel SpeedStep Technology	✓
Processor model * Processor cores	N3350 2	Intel® Clear Video HD Technology (Intel® CVT HD)	✓
Processor threads	2	Intel Clear Video Technology	✓
Processor boost frequency	2,4 GHz	Intel® InTru™ 3D Technology	x
Processor frequency *	1,1 GHz	Intel® Insider™	×
System bus rate	5 GT/s	Intel® Quick Sync Video Technology	/
Processor cache	2 MB	Intel® AES New Instructions (Intel®	
Processor cache type Processor socket	L2 BGA 1296	AES-NI)	✓
Processor lithography	14 nm	Intel Trusted Execution Technology	x
Processor operating modes	64-bit	Intel Enhanced Halt State	✓
Processor series	Intel Celeron N3000 series	Intel VT-x with Extended Page	/
Processor codename	Apollo Lake	Tables (EPT)	•
Thermal Design Power (TDP)	6 W	Intel® Secure Key	✓
Scenario Design Power (SDP)	4 W	Intel Stable Image Platform Program	x
Tjunction	105 °C	(SIPP)	
Maximum number of PCI Express lanes	6	Intel® OS Guard Intel® Clear Video Technology for	•
PCI Express slots version	2.0	Mobile Internet Devices (Intel CVT for MID)	/

Processor		Processor special features	
PCI Express configurations	1x2+2x1, 4x1	Intel 64	✓
ECC supported by processor	x	Execute Disable Bit	✓
Memory		Idle States	✓
Internal memory *	4 GB	Thermal Monitoring Technologies	✓
Internal memory type	LPDDR4-SDRAM	Processor package size	24 x 31 mm
Memory clock speed	1600 MHz	CPU configuration (max)	1
Memory form factor Maximum internal memory *	On-board 4 GB	Embedded options available	✓
	4 GD	UART Intel Virtualization Technology for	✓
Storage Total storage capacity *	32 GB	Directed I/O (VT-d)	✓
Storage media *	eMMC	Intel Smart Idle Technology	×
Flash memory	32 GB	Intel Secure Boot	/
Optical drive type *	×	Intel Smart Connect Technology version	0,00
Card reader integrated	✓	Intel Identity Protection Technology	1.00
Compatible memory cards	MicroSD (TransFlash)	version	1,00
Graphics		Intel Smart Response Technology version	0,00
Discrete graphics card model *	Not available	Intel Secure Boot Technology	1,00
On-board graphics card *	✓ Intol	version Intel Stable Image Platform Program	
On-board GPU manufacturer Discrete graphics card *	Intel X	(SIPP) version	0,00
On-board graphics card model *	Intel® HD Graphics 500	Intel Secure Key Technology version	1,00
On-board graphics card base	200 MHz	Intel Small Business Advantage (SBA) version	0,00
frequency On-board graphics card burst		Intel Virtualization Technology (VT-	/
frequency	650 MHz	x) Intel Rapid Storage Technology	×
On-board graphics card dynamic frequency (max)	650 MHz	Processor ARK ID	95598
Maximum on-board graphics card	8 GB	Conflict-Free processor	✓
memory Number of execution units	12	Battery	
On-board graphics card ID	0x5A85	Battery technology	Lithium-Ion (Li-Ion)
		Number of battery cells	4
On-board graphics card ID		Number of battery cells Battery capacity *	
On-board graphics card ID Audio	0x5A85	Number of battery cells Battery capacity * Power	4 46 Wh
On-board graphics card ID Audio Built-in microphone Camera	0x5A85	Number of battery cells Battery capacity * Power AC adapter power	4 46 Wh 45 W
On-board graphics card ID Audio Built-in microphone	0x5A85	Number of battery cells Battery capacity * Power	4 46 Wh
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric)	0x5A85 ✓	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency	4 46 Wh 45 W 50 - 60 Hz
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network	0x5A85 ✓ 5 MP	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric)	0x5A85 ✓	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards	0x5A85 ✓ 5 MP Wi-Fi 5 (802.11ac) 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards	0x5A85 ✓ 5 MP Wi-Fi 5 (802.11ac) 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓ 307 mm 199 mm
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington 307 mm 199 mm 20,6 mm
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity *	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height Weight *	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington 307 mm 199 mm 20,6 mm
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height Weight * Packaging content	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓ 307 mm 199 mm 20,6 mm 1,25 kg
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity *	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height Weight * Packaging content	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓ 307 mm 199 mm 20,6 mm 1,25 kg
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity * DVI port	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height Weight * Packaging content	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓ 307 mm 199 mm 20,6 mm 1,25 kg
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity * DVI port Combo headphone/mic port	0x5A85	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height Weight * Packaging content	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓ 307 mm 199 mm 20,6 mm 1,25 kg
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity * DVI port Combo headphone/mic port	0x5A85 V 5 MP Wi-Fi 5 (802.11ac) 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n) X 4.1 2 2 X V	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height Weight * Packaging content	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓ 307 mm 199 mm 20,6 mm 1,25 kg
On-board graphics card ID Audio Built-in microphone Camera Front camera Front camera resolution (numeric) Network Wi-Fi Top Wi-Fi standard * Wi-Fi standards Ethernet LAN Bluetooth Bluetooth version Ports & interfaces USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity * DVI port Combo headphone/mic port Performance Motherboard chipset	0x5A85 V 5 MP Wi-Fi 5 (802.11ac) 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n) X 4.1 2 2 X V	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage Security Cable lock slot type Trusted Platform Module (TPM) Weight & dimensions Width Depth Height Weight * Packaging content	4 46 Wh 45 W 50 - 60 Hz 100 - 240 V 2,25 A 20 V Kensington ✓ 307 mm 199 mm 20,6 mm 1,25 kg

			r۵

Operating system installed *

ChromeOS

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.