



Canon EOS 200D SLR Camera Body 24,2 MP CMOS 6000 x 4000 pixels Black

Brand : Canon

Product family: EOS

Article code: 2250C001

Product name : 200D

Canon EOS 200D. Camera type: SLR Camera Body, Megapixel: 24,2 MP, Sensor type: CMOS, Maximum image resolution: 6000 x 4000 pixels. ISO sensitivity (max): 25600. Fastest camera shutter speed: 1/4000 s. Wi-Fi. HD type: Full HD, Maximum video resolution: 1920 x 1080 pixels. Display diagonal: 7,62 cm (3"), Touchscreen. Viewfinder type: Optical. PictBridge. Product color: Black



Picture quality		Viewfinder	
Camera type *	SLR Camera Body	Magnification	0,87x
Megapixel *	24,2 MP	Ports & interfaces	
Sensor type *	CMOS	PictBridge *	✓
Maximum image resolution *	6000 x 4000 pixels	USB version *	2.0
Still image resolution(s) *	6000x4000, 3984x2656,	HDMI *	✓
	2976x1984, 2400x1600,	HDMI connector type	Mini
	5328x4000, 3552x2664,	Microphone in	✓
	2112x1600, 6000x3368,	USB port	✓
	3984x2240, 2976x1680,	Network	
	2400x1344, 4000x4000,	Bluetooth *	✓
	2656x2656, 1984x1984, 1600x1600		✓
Supported aspect ratios	1:1, 3:2, 4:3, 16:9		✓
Total megapixels	25,8 MP		✓
Image sensor size (W x H)	22,3 x 14,9 mm	Wi-Fi *	✓
Image formats supported *	JPG, RAW	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Lens system		Near Field Communication (NFC) *	✓
Lens mount interface	Canon EF, Canon EF-S	Camera	
Focusing		White balance *	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Shade, Tungsten
Focus adjustment *	Auto/Manual	Scene modes *	Candlelight, Children, Food, Portrait, Landscape
Auto focusing (AF) modes *	AI Focus, One Shot Focus, Servo Auto Focus	Shooting modes *	Aperture priority, Auto, Manual, Shutter priority
Auto Focus (AF) points	9	Photo effects *	Black&White
Auto Focus (AF) lock	✓	Self-timer delay *	2,10 s
Auto Focus (AF) assist beam	✓	Brightness adjustment	✓
Exposure		Camera playback	Movie, Slide show
ISO sensitivity (min) *	100	Dioptr correction	✓
ISO sensitivity (max) *	25600	Dioptr adjustment (D-D)	-3 - 1
ISO sensitivity	100, 12800, 25600, Auto	Playback zoom (max)	10x
Light exposure modes *	Auto, Manual	Languages support	Multi
Light exposure control	Program AE	Histogram	✓
Light exposure correction *	± 5EV (1/2EV; 1/3EV step)		
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot		

Exposure		Camera	
Auto Exposure (AE) lock	✓	Live view	✓
Shutter		Image editing	Crop, Resizing
Fastest camera shutter speed *	1/4000 s	Orientation sensor	✓
Slowest camera shutter speed *	30 s	Camera file system	DCF 2.0, DPOF 1.1, Exif 2.3, RAW
Camera shutter type	Electronic	Eye relief	1,9 cm
Flash		Playback modes	Repeat, Slideshow
Flash modes *	Auto, Manual, Red-eye reduction	Slideshow	✓
Flash exposure lock	✓	Built-in processor	✓
Flash guide number	9,8 m	Image processor	DIGIC 7
Flash recharging time	3 s	Windows operating systems supported	✓
Flash sync-speed	1/200 s	Mac operating systems supported	✓
Flash exposure compensation	✓	Design	
Flash exposure correction	±2EV (1/2, 1/3 EV step)	Product color *	Black
Shoe mounting point	✓	Material	Aluminium, Polycarbonate, Resin
Shoe mounting point type	Hot shoe	Battery	
Video		Battery technology *	Lithium-Ion (Li-Ion)
Video recording *	✓	Battery type	LP-E17
Maximum video resolution *	1920 x 1080 pixels	Number of batteries supported	1
HD type *	Full HD	Battery level indicator	✓
Video resolutions	640 x 480, 1280 x 720, 1920 x 1080 640x480@25fps, 1280x720@25fps, 1280x720@50fps, 1920x1080@25fps, 1920x1080@50fps	Operational conditions	
Resolution at capture speed		Operating temperature (T-T)	0 - 40 °C
Analog signal format system	NTSC, PAL	Operating relative humidity (H-H)	0 - 85%
Video formats supported	H.264, MOV, MP4	Weight & dimensions	
Audio		Width	122,4 mm
Built-in microphone *	✓	Depth	69,8 mm
Audio formats supported	AAC, LPCM, PCM	Height	92,6 mm
Memory		Weight (including battery)	453 g
Compatible memory cards *	SD, SDHC, SDXC	Packaging content	
Memory slots	1	AC adapter included *	✓
Display		Bundled software	EOS Utility EOS Lens Registration Tool EOS Web Service Registration Tool EOS Sample Music Digital Photo Professional 4 Picture Style Editor Camera Connect
Display *	TFT	Other features	
Touchscreen *	✓	Power source type	Battery
Display diagonal *	7,62 cm (3")	Technical details	
Display diagonal (metric)	7,7 cm	Self-timer	✓
Display resolution (numeric)	1040000 pixels		
Flip-out screen	✓		
Field of view	100%		
Viewfinder			
Viewfinder type	Optical		



4549292091328



8714574652788

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.