

Allied Telesis AT-GS950/24 Managed



Brand : Allied Telesis

Product code: AT-GS950/24-30

Product name : AT-GS950/24

10/100/1000T x 24 ports WebSmart Switch w/ 2 combo SFP ports (European power cord)

Allied Telesis AT-GS950/24 Managed:

The WebSmart AT-GS950/24 features a Web-based interface that allows you to set up 802.1Q VLANs to segregate traffic, QoS to prioritize mission-critical data such as voice or video packets, and link aggregation to create traffic pipelines. The AT-GS950/24 also provides network monitoring tools such as port mirroring and basic port statistics. Remote product management enables simple monitoring from anywhere you have connectivity. This WebSmart switch provides managed features for simple QoS applications, 24 10/100/1000T ports, and two combo SFP ports for Gigabit connections.

Allied Telesis AT-GS950/24. Switch type: Managed. Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 8000 entries. Networking standards: IEEE 802.1d, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE...

Management features		Performance	
Switch type *	Managed	Internal memory	8 MB
Quality of Service (QoS) support	✓	Flash memory	2 MB
Web-based management	✓	Power over Ethernet (PoE)	
Ports & interfaces		Power over Ethernet (PoE) *	✗
Basic switching RJ-45 Ethernet ports quantity *	24	Other features	
Combo SFP ports quantity	4	Dimensions (WxDxH)	440 x 257 x 43,2 mm
SFP/SFP+ slots quantity	2	Non-operating relative humidity (non-condensing)	5 - 95%
Network		Packet transfer speed	1488000 pps
Networking standards *	IEEE 802.1d, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power requirements	100-240V AC, 50/60Hz
Port mirroring	✓	Networking features	Gigabit Ethernet
Flow control support	✓	Operational conditions	
Link aggregation	✓	Operating temperature (T-T)	0 - 40 °C
Data transmission		Storage temperature (T-T)	-25 - 70 °C
Supported data transfer rates	10/100/1000 Mbps	Operating relative humidity (H-H)	5 - 90%
MAC address table *	8000 entries	Weight & dimensions	
Maximum data transfer rate	1 Gbit/s	Weight	3,24 kg
Packet buffer memory	0,5 MB	Certificates	
Design		Certification	UL 1950 FCC/EN55022 Class A VCCI Class A C-Tick EN60950 (TUV) EN55024 CE
Stackable *	✗		



0767035178455



767035178455

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.