



ATEN CE250A KVM switch Rack mounting Black

Brand : ATEN

Product code: CE250

Product name : CE250A

- Uses Cat 5 cable to connect the local and remote units(up to 150m apart)-We strongly recommend that you use Cat 5 STP cable.
 - Dual Console Operation - Control your system from both the local and remote PS/2 keyboard,mouse and mointor console.
 - Push button selection-sequential selection between local and auto mode.
 - Automatic Gain Control-automatically adjusts signal strength to compensate for distance.
 - Built-in ASIC for greater reliability and compatibility.
 - Supports DDC2B for local monitor (display data channel for communication between graphic card and monitor)
 - Support VGA,SVGA,and Multisync Monitors.
 - Multiplatform support: Windows 2000/XP/Vista and Linux.
- PS/2 KVM Extender

ATEN CE250A KVM switch Rack mounting Black:

CE250 KVM Extender is a console extender with built-in PS/2 and ASIC chip. It allows remote users to connect and access to the server devices via the console. Users will only need to install it by connecting some cables, without using additional tools or software.

| Ports & interfaces | | Operational conditions | |
|-----------------------------|--------------------|------------------------------|--|
| Keyboard port type * | PS/2 | Storage temperature (T-T) | -20 - 60 °C |
| Mouse port type * | PS/2 | Storage humidity | 0 - 80% |
| Performance | | Weight & dimensions | |
| Maximum resolution * | 1280 x 1024 pixels | Weight | 330 g |
| Design | | Other features | |
| Rack mounting * | ✓ | Connectivity technology | Wired & Wireless |
| Product colour * | Black | Power supply type | DC |
| Cable length | 1.8 m | I/O ports | 2 x 6-pin Mini-DIN Female 1 x HDB-15 Female 1 x SPHD-15 Female 1 x DC Jack 1 x RJ45 Female |
| LED indicators | ✓ | | |
| Power | | Dimensions (WxDxH) | 125 x 81.5 x 25 mm |
| Power consumption (typical) | 1.25 W | Compatible operating systems | Windows 2000/XP/Vista Linux |
| Operational conditions | | Power requirements | 5.0V |
| Operating temperature (T-T) | 0 - 50 °C | | |





4710423770126

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.