

Brother HL-L2340DW laser printer 2400 x 600 DPI A4 Wi-Fi

Brand: Brother Product code: HL-L2340DW

Product name: HL-L2340DW

Compact High Quality Mono Laser Printer + Wi-Fi

Brother HL-L2340DW laser printer 2400 x 600 DPI A4 Wi-Fi:

A perfect Mono Laser printer for connected Small Offices. Print high-quality documents in black and white with the touch of a button with this tablet and Wi-Fi enabled, mobile print compatible machine.

With print speeds of up to 26ppm your documents can be ready before you arrive at the printer to pick them up. The 250 sheet paper tray allows you to spend more time creating your documents instead of reloading an empty paper tray to print them.

Also prepare to print from anywhere, using the Brother iPrint&Scan app, Google Cloud Print, Apple AirPrint and Wi-Fi Direct you can send your documents to print using your tablet or mobile device.


With efficiency in mind, the double-sided printing feature and optional, high-yield toner cartridges you can expect reduced waste and costs.





Printing		Performance	
Duplex printing mode	Auto	Built-in processor	✓
Colour *	×	Processor family	ARM Cortex
Print technology *	Laser	Processor	ARM9
Duplex printing *	✓	Processor frequency	266 MHz
Maximum resolution *	2400 x 600 DPI	Sound pressure level (printing)	49 dB
Print speed (black, normal quality, A4/US Letter) *	26 ppm	Noise level (idle) Design	30 dB
Duplex print speed (black, normal quality, A4/US Letter)	8.5 ppm	Product colour *	Black
Warm-up time	9 s	Certification	Nordic Swan
N-up printing	2, 4, 6, 9, 16, 25	Power	
Features		Power consumption (printing) *	455 W
Recommended duty cycle Printing colours * Number of print cartridges * Country of origin	250 - 2000 pages per month Black 1 Vietnam	Power consumption (standby) Power consumption (PowerSave) AC input voltage AC input frequency	58 W 5.4 W 220 - 240 V 50 - 60 Hz
Input & output capacity			
Total input capacity * Total output capacity * Paper input type Multi-Purpose tray Multi-Purpose tray input capacity	250 sheets 100 sheets Paper tray		
Paper handling			
Maximum ISO A-series paper size * Maximum print size	A4 210 x 297 mm		
Paper tray media types *	Bond paper, Envelopes, Labels, Plain paper, Recycled paper, Thick paper, Thicker paper, Thin paper		
ISO A-series sizes (A0A9) *	A4, A5, A6		
Non-ISO print media sizes	Executive, Letter		
JIS B-series sizes (B0B9)	B5		
Custom media width	76.2 - 215.9 mm		
Custom media length	127 - 355.6 mm		
Paper tray media weight	60 - 105 g/m ²		

Paper handling		System requirements	
Multi-Purpose Tray media weight	60 - 163 g/m²	_,	Windows 7 Home Basic, Windows 7
Ports & interfaces	00 103 g/m		Home Basic x64, Windows 7 Home
Standard interfaces	USB 1.1, USB 2.0, Wireless LAN		Premium, Windows 7 Home Premium x64, Windows 7
Direct printing *	✓		Professional, Windows 7 Professional x64, Windows 7
USB 2.0 ports quantity	1		Starter, Windows 7 Starter x64,
Network			Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows
Network ready	1		8 Enterprise, Windows 8 Enterprise
Wi-Fi *	<i>'</i>		x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1,
Ethernet LAN connection *	×	Windows anarating systems	Windows 8.1 Enterprise, Windows
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Windows operating systems supported	8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows
Security algorithms	128-bit WEP, 64-bit WEP, SMTP- AUTH, SNMP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP, WPS ARP, RARP, BOOTP, DHCP,		8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home
Supported network protocols (IPv4)	ARP, NARP, BOOTP, DITCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c/v3, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services (Print)		Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Supported network protocols (IPv6)	NDP, RA, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c/v3, HTTP Server, TFP Client and Server,	Mac operating systems supported	Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
		Linux operating systems supported	✓
	SMTP Client, ICMPv6, Web Services (Print)		Windows Server 2003, Windows Server 2003 x64, Windows Server
Web-based management Mobile printing technologies	✓ Apple AirPrint, Brother iPrint & Scan, Google Cloud Print	Server operating systems supported	2008, Windows Server 2008 R2, Windows Server 2008 x64, Windows Server 2012, Windows Server 2012 R2
Performance		Minimum storage drive space	80 MB
Performance Internal memory *	32 MB	Minimum storage drive space Operational conditions	
	32 MB		
	32 MB	Operational conditions	80 MB
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	80 MB 10 - 32 °C 0 - 40 °C 20 - 80%
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T)	80 MB 10 - 32 °C 0 - 40 °C
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90%
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity	80 MB 10 - 32 °C 0 - 40 °C 20 - 80%
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90%
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm 504 mm
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm 504 mm
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm 504 mm 7.83 kg
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content Drivers included	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm 504 mm 7.83 kg
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content Drivers included Quick start guide	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm 504 mm 7.83 kg
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package weight Packaging content Drivers included Quick start guide Cables included	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm 504 mm 7.83 kg
	32 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage humidity Sustainability Sustainability certificates Weight & dimensions Width Depth Height Weight Packaging data Package width Package depth Package height Package weight Packaging content Drivers included Quick start guide Cables included Bundled software	80 MB 10 - 32 °C 0 - 40 °C 20 - 80% 10 - 90% ENERGY STAR 440 mm 290 mm 500 mm 6.82 kg 286 mm 441 mm 504 mm 7.83 kg


















Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.