

## ASUS RAMPAGE/EXTREME motherboard LGA 775 (Socket T) ATX

**Brand :** ASUS

**Product code:** RAMPAGE/EXTREME

**Product name :** RAMPAGE/EXTREME

RAMPAGE/EXTREME, Intel Socket 775, Intel X48 / ICH9R, Intel Core2 Extreme/Core2 Quad/ Core2 Duo/Pentium dual-core/Celeron dual-core /Celeron Processors, 4 x DIMM, Max. 8GB, DDR3 2000/1800/1600/1333/1066/800, 2x PCIe 2.0 x16, 3 x PCIe x1, 2 x PCI 2.2, Dual Gigabit LAN, ATX Form Factor, (DK)

ASUS RAMPAGE/EXTREME motherboard LGA 775 (Socket T) ATX:

### The Ultimate Overclocking Board for Tweaking Fun

- Intel® Core™ 2 Extreme / Core™ 2 Quad / Core™ 2 Duo / Pentium® Extreme / Pentium® D / Pentium® 4 Processors
- Intel® X48/ICH9R
- Dual-channel DDR3 2000(O.C.)/1800(O.C.)/1600/1333/1066/800 MHz
- Fusion Block System
- Extreme Engine
- TweakIt
- BIOS Flashback
- iROG
- SupremeFX X-Fi 8-ch Audio

ASUS RAMPAGE/EXTREME. Processor manufacturer: Intel, Processor socket: LGA 775 (Socket T). Memory, maximum: 8 GB, ECC compatibility: ECC & Non-ECC. RAID levels: 0, 1, 10. Network interface: Dual Gigabit Ethernet. Motherboard form factor: ATX, Audio chip: ADI AD2000B, Power source type: ATX



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	Firewire (IEEE 1394) ports	1
Processor socket *	LGA 775 (Socket T)	<b>Network</b>	
<b>Memory</b>		Network interface	Dual Gigabit Ethernet
Number of memory slots *	4	<b>Features</b>	
ECC compatibility	ECC & Non-ECC	Audio chip	ADI AD2000B
Memory, maximum *	8 GB	Motherboard form factor *	ATX
<b>Storage controllers</b>		Power source type	ATX
RAID levels	0, 1, 10	<b>Expansion slots</b>	
<b>Internal I/O</b>		Expansion slots	2 x PCIe 2.0 x16, 3 x PCIe x1 2 x PCI 2.2
USB 2.0 connectors *	3	<b>BIOS</b>	
Number of SATA connectors	8	BIOS type *	AMI
ATX Power connector (24-pin)	✓	BIOS memory size	16 Mbit
Power fan connector	✓	<b>Weight &amp; dimensions</b>	
CPU fan connector	✓	Width	305 mm
Number of chassis fan connectors	3	Depth	245 mm
Chassis intrusion connector	✓	<b>Packaging content</b>	
Number of IEEE1394 connectors	1	Drivers included	✓
<b>Rear panel I/O ports</b>		<b>Other features</b>	
USB 2.0 ports quantity *	6	S/PDIF in port	✗
Ethernet LAN (RJ-45) ports *	2	Controller 2nd interface type	UltraDMA 133/100/66/33
eSATA ports quantity	1	Controller interface type	SATA
PS/2 ports quantity	1	Floppy disk drive connector	✓
		Manageability features	WOL, WOR, Chasis Intrusion, PXE

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.