## Canon

## Canon CanoScan 9000F Mark II Flatbed scanner 9600 x 9600 DPI A4 Black, Silver

Brand : Canon Product family: CanoScan Product code: 6218B009

Product name: 9000F Mark II

Flatbed, A4, CCD, 9600 x 9600 dpi, USB, 15 W, 4580 g, Black/Silver Canon CanoScan 9000F Mark II. Maximum scan size:  $210 \times 297$  mm, Optical scanning resolution:  $9600 \times 9600$  DPI, Enhanced scan resolution:  $19200 \times 19200$  DPI. Scanner type: Flatbed scanner, Product colour: Black, Silver. Sensor type: CCD, Light source: White LED, Scan file formats: PDF. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4. Standard interfaces: USB 2.0



Scanning		Ports & interfaces	
Maximum scan size * 210 x 297 mm  Optical scanning resolution * 9600 x 9600 DPI  Enhanced scan resolution 19200 x 19200 DPI  Colour scanning ✓  Duplex scanning * X  Input colour depth 48 bit  Output colour depth 48 bit  Film scanning ✓  Flatbed scan speed (b/w, A4) 7 sec/page	9600 x 9600 DPI 19200 x 19200 DPI	USB port * USB version	2.0
		Standard interfaces  Power	USB 2.0
	48 bit 48 bit ✓	Power supply type * Power consumption (typical) Power consumption (standby) AC input frequency Input voltage	AC 15 W 0,9 W 50 - 60 Hz 100-240 V
Design		Weight & dimensions	
Scanner type * Product colour *	Flatbed scanner Black, Silver	Width Depth	480 mm 112 mm
Performance Sensor type * Light source	CCD White LED	Height Weight	272 mm 4,58 kg
		System requirements	
Scan file formats Scan to Scan drivers	PDF E-mail, File, OCR ScanSnap	Windows operating systems supported	Windows 7 Home Basic, Windows 7 Home Premium, Windows 7 Professional, Windows 7 Starter, Windows 7 Ultimate, Windows 8, Windows 8 Enterprise, Windows 8 Pro, Windows RT, Windows Vista Business, Windows Vista Enterprise, Windows Vista Home Basic, Windows Vista Home Premium, Windows Vista Ultimate, Windows XP Home, Windows XP Professional
Paper handling  Maximum ISO A-series paper size * ISO A-series sizes (A0A9)	A4 A4		
		Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion
		Operational conditions	
		Operating relative humidity (H-H) Operating temperature (T-T)	10 - 90% 50 - 95 °F











## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.