## **D-Link DSL-2750B wireless router Fast Ethernet**

Brand : D-Link

Product code: DSL-2750B

Product name : DSL-2750B

DSL-2750B - 802.11b/g/n, 4x RJ-45, Fast Ethernet, USB, 300 Mbps, ADSL2+ D-Link DSL-2750B. Top Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN data transfer rate (max): 300 Mbit/s, Wi-Fi standards: 802.11b, 802.11g, Wi-Fi 4 (802.11n). Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Security algorithms: 128-bit WEP, 64-bit WEP, 802.1x RADIUS, WPA, WPA2. Supported network protocols: IP/ICMP/TCP/UDP. LED indicators: DSL, LAN, Power, USB, WLAN

## WAN connection Design LED indicators DSL WAN \* DSL, LAN, Power, USB, WLAN 1 On/off switch Wireless LAN features Certificates Top Wi-Fi standard \* Wi-Fi 4 (802.11n) WLAN data transfer rate (max) \* 300 Mbit/s C-Tick, CE, FCC, IC, WHQL, Wi-Fi, Certification WPS Wi-Fi standards 802.11b, 802.11g, Wi-Fi 4 (802.11n) Packaging content Network AC adapter included 1 Ethernet LAN \* Ethernet LAN interface type \* Fast Ethernet Antenna Ethernet LAN data rates 10.100 Mbit/s External Antenna design \* 10/100Base-T(X) Cabling technology Antennas quantity 2 IEEE 802.11b, IEEE 802.11g, IEEE Networking standards Features 802.11n PPTP/IPSec/L2TP VPN support Firmware upgradeable 1 DSL features Power ADSL2+ 1 Output voltage 12 V Power over Ethernet (PoE) x Ports & interfaces **Operational conditions** Ethernet LAN (RJ-45) ports \* 4 RJ-11 ports quantity 1 Operating temperature (T-T) 0 - 40 °C DC-in jack -20 - 70 °C Storage temperature (T-T) Operating relative humidity (H-H) 5 - 95% Management features Weight & dimensions Web-based management 1 Width 127,8 mm Quality of Service (QoS) support Depth 182,8 mm Security Height 32 mm 128-bit WEP, 64-bit WEP, 802.1x Weiaht 236 g Security algorithms RADIUS, WPA, WPA2 Other features Stateful Packet Inspection (SPI) WLAN data transfer rates supported 300 Mbit/s System event log 2,4 - 2,4835 GHz Frequency range DMZ support USB ports quantity 1 Network address translation (NAT) 1 Input current 1 A Protocols Frequency band 2.4 GHz Bandwidth 2.4 GHz DHCP client 1 Rack mounting × DHCP server Upstream data rate 1 Mbit/s Universal Plug and Play (UPnP)



## Protocols

Supported network protocols

IP/ICMP/TCP/UDP

Other features

Downstream data rate xDSL connection

24 Mbit/s

**Catalog Object Cloud** 



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.