

Buffalo LinkStation 420 NAS Marvell Armada 370 0,5 GB DDR3 4 TB HDD Black

Brand : Buffalo

Product code: LS420D0402-EU

Product name : LinkStation 420

LinkStation 420 series: Network Attached Storage, 4TB

Buffalo LinkStation 420. Type: NAS. Processor family: Marvell, Processor model: Armada 370, Processor frequency: 1,2 GHz. Internal memory: 0,5 GB, Internal memory type: DDR3. Total installed storage capacity: 4 TB, Installed storage drive type: HDD



| Storage | | Design | |
|--------------------------------------|--|---|-------------|
| Storage drive capacity * | 2 TB | Product colour | Black |
| Storage drive interface * | Serial ATA | LED indicators | ✓ |
| Maximum supported storage capacity | 8 TB | Performance | |
| RAID support * | ✓ | Type * | NAS |
| RAID levels | 0, 1, JBOD | Backup function * | ✓ |
| Hot-swap drive bays | ✗ | Built-in BitTorrent client | ✓ |
| Storage drives installed * | ✓ | Powerful backup NovaBACKUP Professional | ✓ |
| Total installed storage capacity * | 4 TB | Software | |
| Number of storage drives installed * | 2 | Bundled software | TimeMachine |
| Number of storage drives supported * | 2 | Windows operating systems supported | ✓ |
| Installed storage drive type * | HDD | Mac operating systems supported | ✓ |
| Supported storage drive types * | HDD | Power | |
| Processor | | Power supply unit (PSU) capacity | 48 W |
| Processor family * | Marvell | Number of power supply units | 1 |
| Processor model * | Armada 370 | Redundant power supply (RPS) support | ✗ |
| Processor frequency * | 1,2 GHz | Power consumption (typical) | 26 W |
| Number of processors installed | 1 | AC input voltage | 100-240 V |
| Memory | | AC input frequency | 50 - 60 Hz |
| Internal memory * | 0,5 GB | Weight & dimensions | |
| Internal memory type | DDR3 | Width * | 87 mm |
| Network | | Depth * | 205 mm |
| Ethernet LAN * | ✓ | Height * | 128 mm |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Weight | 2,4 kg |
| Wi-Fi | ✗ | Operational conditions | |
| Supported network protocols | TCP/IP, SMB/CIFS, FTP, HTTP/HTTPS, AFP | Operating temperature (T-T) | 5 - 35 °C |
| Ports & interfaces | | Operating relative humidity (H-H) | 20 - 80% |
| USB 2.0 ports quantity | 1 | | |

| Ports & interfaces | | Other features | |
|------------------------------|---|--|---|
| Ethernet LAN (RJ-45) ports * | 1 | Digital Living Network Alliance (DLNA) certified | ✓ |

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.