ASUS H61M-K Intel® H61 LGA 1155 (Socket H2) micro ATX

Brand : ASUS **Product code:** 90MB0FP0-M0EAY0

Product name: H61M-K

Intel H61 Chipset , Socket LGA 1155, 2x DIMM (up to 16GB DDR3), 4x USB 2.0, DVI-D, D-Sub, Gigabit LAN, micro-ATX

ASUS H61M-K. Processor manufacturer: Intel, Processor socket: LGA 1155 (Socket H2), Compatible processor series: Intel® Celeron® G, Intel® Pentium®. Supported memory types: DDR3-SDRAM, Maximum internal memory: 16 GB, Memory slots type: DIMM. Supported storage drive interfaces: SATA II. Maximum resolution: 2048 x 1536 pixels. Ethernet interface type: Gigabit Ethernet, LAN controller: Realtek RTL8111F





_			
Processor		Internal I/O	
Processor manufacturer *	Intel	Number of chassis fan connectors	1
Processor socket *	LGA 1155 (Socket H2)	Rear panel I/O ports	
Compatible processor series *	Intel® Celeron® G, Intel® Pentium®	USB 2.0 ports quantity *	4
Maximum number of SMP processors	1	Ethernet LAN (RJ-45) ports quantity *	1
Supported processor sockets Processor thermal power (max)	LGA 1155 (Socket H2) 77 W	PS/2 ports quantity VGA (D-Sub) ports quantity *	2 1
Memory		DVI-D ports quantity *	1
Supported memory types *	DDR3-SDRAM	Headphone outputs Microphone in	2 ✓
Number of memory slots *	2	•	•
Memory slots type	DIMM	Network	
Memory channels	Dual-channel	Ethernet LAN connection	✓
ECC compatibility	Non-ECC	Ethernet interface type	Gigabit Ethernet
Supported memory clock speeds	1066,1333,1600 MHz	LAN controller	Realtek RTL8111F
Maximum internal memory *	16 GB	Features	
Supported memory module capacities	4GB, 8GB	Motherboard chipset *	Intel® H61
Unbuffered memory	✓	Audio output channels *	7.1 channels
Flash memory	64 MB	Component for *	PC
Storage Controllers		Motherboard form factor * Motherboard chipset family *	micro ATX Intel
Supported storage drive interfaces	* SATA II	Cooling type	Passive
Graphics		Power source type	ATX
Maximum resolution	2048 x 1536 pixels	Expansion Slots	
Internal I/O		PCI Express x1 (Gen 2.x) slots	2
USB 2.0 connectors *	2	PCI Express x16 slots	1
Number of SATA II connectors	4	BIOS	
Front panel audio connector	✓	BIOS type *	UEFI

Internal I/O		BIOS	
ATX Power connector (24-pin)	✓	ACPI version	2.0a
CPU fan connector	✓	Clear CMOS jumper	✓
		Weight & Dimensions	
		Width	226 mm
		Depth	175 mm



4716659587590

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.