GIGABYTE AORUS P1200W power supply unit 1200 W 20+4 pin ATX ATX Black

Brand : GIGABYTE Product code: GP-AP1200PM

Product name: AORUS P1200W

- Digital LCD monitor
- Fully modular design
- 100% Japanese capacitors
- Compact size design
- 140mm smart double ball bearing fan
- Fan dust removal function
- Single +12V rail
- OVP/OPP/SCP/UVP/OCP/OTP protection

Aorus P1200w 80+ platinum modular, 100-240 V, 100,000 hours, Active PFC, black GIGABYTE AORUS P1200W. Total power: 1200 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,650 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Platinum. Product colour: Black, Cooling type: Active, Fan diameter: 14 cm. Cables included: CPU, PCIe, Peripheral (Molex), SATA





Energy Management		Ports & interfaces	
Total power *	1200 W	Floppy drive power connector	2
AC input voltage *	100 - 240 V	Floppy disk drive connector	✓
AC input frequency	50 - 60 Hz	Floppy disk drive cable length	15 cm
Input current	15 - 7.5 A	Cabling type	Fully-Modular
Power Factor Correction (PFC) type	Active	Performance	
Hold time	16 ms		OO DI LIC DIstissuss
Efficiency	92%	80 PLUS certification *	80 PLUS Platinum
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage	Supported motherboard form factors	ATX
Ports & interfaces		Purpose *	PC
Motherboard power connector *	20+4 pin ATX	Power supply unit (PSU) form factor *	ATX
Motherboard power cable length	61 cm	ATX version	2.31
Number of SATA power connectors	16	Bearing technology	DBB
SATA power cable length	150,650 mm	Mean time between failures (MTBF)	100000 h
Peripheral (Molex) power connectors (4-pin) *	6	Design	
Peripheral (Molex) power cable length	120,150,600 mm	Product colour Cooling type	Black Active
EPS power connector (4+4 pin)	✓	Fan diameter	14 cm
PCI Express power connectors (6+2		Number of fans	1 fan(s)
pin)	10	Fan location	Тор
PCI Express power cable length	65 cm	Illumination	✓
CPU power connector (4+4 pin)	✓	Packaging Content	
CPU power cable length	65 cm	Cables included	CPU, PCIe, Peripheral (Molex), SATA
ATX power connector (20+4 pin)	✓		CPO, PCIe, Periprieral (Molex), SATA
		Weight & Dimensions	
		Width	150 mm
		Depth	86 mm
		Height	160 mm

LOQ	istics	aata

Harmonized System (HS) code

84733020



4719331552251

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.