

## Fujitsu fi-6770 Flatbed & ADF scanner A4

**Brand : Fujitsu Product code:** PA03576-B005

**Product name:** fi-6770

fi-6770 Color Scanner: Duplex Document Scanning - ADF; 600 dpi; 90 ppm/180 ipm

Fujitsu fi-6770 Flatbed & ADF scanner A4:

## Intelligent scanning for the intelligent office

- -Fast scanning up to 90 ppm/180 ipm in color or monochrome, landscape.
- -Ultrasonic double-feed detection with advanced control.
- -Loaded with "intelligent" functions for more efficient scanning.
- -Advanced image processing in hardware with color graphics adapter (CGA).
- -Valuable bundled software tools and applications including Kofax® VRS 4.2 Professional.
- -Service options to fit specific requirements and budget including Next Business Day, 4-hour or 24/7 contracts available.

Fujitsu fi-6770. Scan size flatbed (maximum): 297,18 x 431,8 mm, Input colour depth: 24 bit. Scanner type: Flatbed & ADF scanner. Sensor type: CCD, Duty cycle (monthly, A4): 450000 pages per month, Scan drivers: TWAIN. Auto document feeder capacity: 200 sheets. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4

Scanning		Power	
Scan size flatbed (maximum) *	297,18 x 431,8 mm	Power consumption (standby)	6 W
Color scanning	✓	Weight & dimensions	
Duplex scanning *	✓	Width	500,4 mm
Input colour depth	24 bit	Depth	342,9 mm
Film scanning	×	Height	690,9 mm
Fax resolution black	256	Weight	35 kg
Design		Packaging content	
Scanner type *	Flatbed & ADF scanner	Bundled software	Adobe Acrobat Standard, VRS Professional + Bar Code, ScandAll PRO, QuickScan Pro
Performance			
Sensor type *	CCD	System requirements	
Duty cycle (monthly, A4) Scan drivers	450000 pages per month TWAIN	Compatible operating systems	Win 98 SE/2000/NT/XP
Input capacity		Operational conditions	
Auto document feeder capacity	200 sheets	Operating temperature (T-T)	5 - 35 °C
, ,		Operating relative humidity (H-H)	20 - 80%
Paper handling  Maximum ISO A-series paper size *	A4	Maximum operating temperature range	42 - 95 °F
ISO A-series sizes (A0A9)	A4 A4	Other features	
Letter	1	Power requirements	AC 100 - 240V. 50 / 60 Hz
Power		Sheet feed maximum output	120 "
Power consumption (typical)	216 W	Scan size (ADF), maximum (imperial)	297,2 x 431,8 mm (11.7 x 17")
		Scan size ADF (minimum)	50,8 x 76,2 mm (2 x 3")

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.