



HP LP2065 20-inch LCD Monitor écran plat de PC 51 cm (20.1") 1600 x 1200 pixels

Marque : HP

Code produit: EF227AT

Nom du produit : LP2065 20-inch LCD Monitor

HP LP2065 20-inch LCD Monitor

HP LP2065 20-inch LCD Monitor. Taille de l'écran: 51 cm (20.1"), Résolution de l'écran: 1600 x 1200 pixels. Écran: LCD. Temps de réponse: 8 ms, Angle de vision horizontal: 178°, Angle de vision vertical: 178°



Écran		Poids et dimensions	
Taille de l'écran *	51 cm (20.1")	Poids (avec support)	9,2 kg
Résolution de l'écran *	1600 x 1200 pixels	Largeur (sans support)	443 mm
Écran tactile *	✗	Profondeur (sans support)	87 mm
Luminosité de l'écran (typique)	300 cd/m²	Hauteur (sans support)	345 mm
Temps de réponse *	8 ms	Poids (sans support)	5,75 kg
Taux de contraste *	800:1	Largeur du cadre (côté)	1,3 cm
Angle de vision horizontal	178°	Autres caractéristiques	
Angle de vision vertical	178°	Pays d'origine	Chine
Pas de pixel	0.255	Écran	LCD
Domaine de numérisation horizontale	30 - 94 kHz	Système audio	No audio included at platform level
Fréquence de balayage vertical	48 - 85 Hz	Synthoniseur TV intégré	✗
Fréquence de balayage	Horizontal frequency: 30-94 kHz (VGA), 30-92 kHz (DVI), Vertical frequency: 48-85 Hz (VGA), 30-92 kHz (DVI)	Dimensions (L x L x H)	442 x 86,9 x 344,9 mm (17.4 x 3.42 x 13.6")
multimédia		Exigences d'alimentation	90 - 132 VAC & 195 - 265 VAC, 50 - 60 Hz
Haut-parleurs intégrés *	✗	Résolution recommandée en fréquence Preset VESA Graphic Modes (non-interlaced): 1600 x 1200 @ 60 Hz-75 Hz (analog input), 1280 x 1024 @ 60 Hz-75 Hz-85 Hz, 1280 x 960 @ 60 Hz, 1152 x 900 @ 66 Hz, 1024 x 768 @ 60 Hz-75 Hz-85 Hz, 800 x 600 @ 60 Hz-85 Hz, 640 x 480 @ 60 Hz-75 Hz-85 Hz; Text Mode: 720 x 400 @ 70 Hz; MAC Mode: 1152 x 870 @ 75 Hz, 832 x 624 @ 75 Hz; SUN Mode: 1152 x 900 @ 66 Hz	
Appareil photo intégré *	✗		
Design		Type de Connecteur d'entrée vidéo	Two connectors, dual DVI-I (VGA analog and digital)
position de marché *	Professionnel	Audio inclus	No audio included at platform level
Connectivité		Caractéristiques de sécurité	Kensington Lock-ready
Ports E/S	One upstream, four downstream USB 2.0 Hub ports (cable included)		
Nombre de ports VGA (D-Sub)	2		
Ergonomie			
Norme VESA	100 x 100 mm		

Ergonomie		Autres caractéristiques	
Plug and Play	✓		Input select, auto adjust/OSD up, OSD down, OSD menu select, power Brightness, contrast, positioning, color temperature, individual color control, serial number display, full screen resolutions, clock, clock phase, video picture-in-picture (size and position), input selection (includes separate direct access key for dedicated swap between inputs 1 and 2), factory reset
Plage d'inclinaison et de pivotement	-5° to 25° vertical tilt, ±45° swivel, pivot/landscape rotation, 13 cm height adjust, detachable base	Commandes d'utilisateur	
Puissance			
Consommation électrique typique *	75 W		
Conditions environnementales			
Température d'opération	10 - 35 °C	Bande passante vidéo	202 MHz
Température hors fonctionnement	-10 - 60 °C	Dimensions du produit avec socle (L x P x H)	442 x 220,2 x 553,7 mm (17.4 x 8.67 x 21.8")
Humidité relative de fonctionnement (H-H)	20 - 80%	Code UNSPSC	43211501
Taux d'humidité relative (stockage)	5 - 85%	Certification	Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 9241-3,7,8 VDT Guidelines, ISO 13406-2 Pixel Defect Guidelines, Mexican NOM Approval, MIC Requirements (New Zealand), MPR-II Compliant, Nordic Approvals (Nemko, Fimko, Demko, Semko), PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 03 (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Windows Certification (Microsoft Windows 98, Microsoft Windows 2000, and Microsoft Windows XP)
		Client léger	
		Fréquence du processeur	2 GHz



0882780066878



882780066878



0886111207732



886111207732



0882780066885



882780066885



0882780066892



882780066892



0882780066915



882780066915



0882780066908



882780066908

Disclaimer: The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party Websites that are linked to the Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.