

Lenovo ThinkCentre E50-00 | Pentium | J2900 4 GB DDR3-SDRAM 500 GB HDD Windows 8.1 | PC | PC |

Control Contro

□□□ **:** E50-00





00000000 *	Intel	0000000 *	
000000 *		000000	
0000000 *	J2900		Realtek ALC662-VD
	4		PC
	4		
	2.66 GHz		Minds of 1
00000 00000000 *	2.41 GHz BGA 1170	0000000 *	Windows 8.1
	2 MB		
000000000 00000000000	L2	0000®0000000000000000SBA0	×
FSBNNN	X	0000® 0000000000(WiDi) 000000	×
	22 nm	0000®640000000	✓
	32-bit, 64-bit	 ®SpeedStep	√
	□□□□® Pentium J2000 Series for		×
	Desktop	nnnn® InTru™3d nnnnn	×
000000000	Bay Trail		
000000000000 TDP 0	10 W	□□□□® Insider™	X
00000000	105 °C	0000® 00000000 HD 000000	×
PCI Express	2.0	0000® 000000000000	×
PCI Express	4	DDD ® VT-x with Extended Page Tables (EPT)	×
PCI Express□□	1x4	, ,	/
0000000000000	1		
	B3		×
0000000000	8 GB	ngge Platform Program (SIPP)	×
	DDR3L-SDRAM	□□□□®AES-NI□New Instructions□	×
	1333 MHz 21.3 GB/∏		
	_		×
	X		✓
			×
0000 *	4 GB	0000 ® 000000000000	×

0000		0000000000	
000000 *	8 GB		×
	DDR3-SDRAM	DDD® Enhanced Halt State	×
	1 x 4 GB	0000® 0000000000000	×
	1x SO-DIMM	0000 ® 0000000000000000000000000000000	×
00000000 0000000	1600 MHz		25 X 27 mm
		0000000	SR1SB
	500 CD	0000000PAE0	36 🖂 🖂
000000000 * 00000000 *	500 GB HDD		1
	DVD±RW	00000001MC000000 0000®00000000000000	22 nm
	1	[](Directed I/O[[VT-d)	×
HDD_	1	0000 ® 0000000000000000000000	0.00
HDD[[[500 GB		
HDD0000000	SATA	Program (SIPP) [[[]]	0.00
HDD[][7200 RPM 3.5"	0000 ® 00000000000000(VT-x)	✓
HDD[[[[]	3.3	0000®000000000000000SBA0000	0.00
000000			•
000000000000000000000000000000000000000	/	0000	X
		@RST)	×
00000000000000000000000000000000000000	0000	□□□□ARK ID	78868
	896 MHz	00000® 0000000000000000000000000000000	×
	896 MHz	® (×
000000000000000000000000000000000000000	2		×
00000000000000000000000000000000000000	11.2		X
		0000 ® 00000000000000	×
LAN *	✓		✓
	10,100,1000 Mbit/□	DODD®My WiFi DODDD	×
00000000000	10/100/1000Base-T(X)		×
000/0000000			×
USB 2.0 □□□□ *	4		✓
USB 3.2 (3.1000) 000A000 *	1		
VGA[[[[[]]]]	1		100 - 240 V
DVI LAN (RJ-45)	X 1		50 - 60 Hz
	·	00/00	
	1		160 mm
	- •	*	425.8 mm
	✓	00 *	386.5 mm
	1	*	9.58 kg
00000		000000	
PCI Express x1 [[[[[]]]	1	0000	×
PCI Express x16 [][]	1		×
000000 *	0000		v
	X	*	X
	1	0000	
0005.25000	1		1 VT v
000000000	✓	00008 00000000000000000000000000000000	VT-x
	Kensington		





888965246363

0888965246363

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.