

**Product code:** 3549D-1128B

Publication date: 11-AUG-2025. Prints or copies of Information are only valid on the printed Publication date

Processor		Processor features	
Processor architecture	Broadwell	Intel® AES encryption engine (Intel® AES- NI)	✗
Cache architecture	DMI2	Intel vPro™ processor support	✗
FSB architecture	✗	Processor support for Intel vPro™	✓
Processor	E0	Intel VT-x processor support (EPT) mode	✓
Processor power (TDP)	15 W	Intel vPro™ processor support	✗
Processor power (TDP) mode	10 W	Intel® vPro™ support	✓
Processor power (TDP) mode	0,6 GHz	Intel TSX-NI	✗
Processor	105 °C	Intel vPro™ processor support (SIPP)	✗
PCI architecture	12	Intel® OS support	✗
PCI architecture	2.0	Processor support for Intel vPro™	✓
PCI architecture	2x4, 4x1	Processor support for Intel vPro™	✓
Processor support for ECC	✗	Processor support for Intel vPro™	✓
Memory		Memory features	
Processor support *	4 GB	Intel 64	✓
Processor support	DDR3L-SDRAM	Processor support for Intel vPro™	✓
Processor support	1600 MHz	Processor support for Intel vPro™	✓
Processor support	SO-DIMM	Processor support for Intel vPro™	✓
Processor support (Processor x Processor)	1 x 4 GB	Processor support for Intel vPro™	40 x 24 x 1.3 mm
Processor support	1x SO-DIMM	Processor support for Intel vPro™	SSE4.1, SSE4.2
Processor support	8 GB	Processor support for Intel vPro™	SR215
Storage		Storage features	
Processor support *	500 GB	CPU support for Intel vPro™ (Processor support)	1
Processor support *	HDD	Processor support for Intel vPro™	✗
Processor support HDDs	1	Processor support for Intel vPro™	14 nm
HDD architecture	500 GB	Processor support for Intel vPro™	✓
HDD architecture	SATA	Intel vPro™ processor support	1,00
HDD rpm	5400 RPM	Intel vPro™ processor support	0,00
HDD rpm	2.5"	Intel vPro™ processor support	0,00
Processor support	DVD support	Intel vPro™ processor support	0,00
Processor support	✓	Intel vPro™ processor support	1,00
Processor support	SD	Intel vPro™ processor support	0,00
Graphics		Graphics features	
Processor support	NVIDIA® GeForce® GT 820M	Intel vPro™ processor support	0,00
Processor support	2 GB	Intel TSX-NI support	0,00
Processor support	GDDR3	Processor support for Intel vPro™	✓
Processor support	✓	Intel vPro™ processor support	✗
Processor support	✓	Intel vPro™ processor support	✓
Processor support	Intel® HD Graphics	Intel Rapid Storage Technology	✗
Processor support	Intel® HD Graphics	Intel vPro™ processor support	✓
Processor support	100 MHz	Processor support for Intel vPro™	84809
Processor support	800 MHz	Processor support for Intel vPro™	✓
Processor support	11.2/12	Processor support for Intel vPro™	✓
Number of discrete graphics cards supported	1	Processor support for Intel vPro™	✓
Number of discrete graphics cards installed	1	Processor support for Intel vPro™	✓
Audio		Audio features	
Processor support	Wave MaxxAudio	Processor support for Intel vPro™	65 W
Processor support	2	Processor support for Intel vPro™	50 - 60 Hz
		Processor support for Intel vPro™	100 - 240 V
		Processor support for Intel vPro™	19.5 V
		Processor support for Intel vPro™	DC-in support

Power		Connectivity	
Power consumption	2 W	Power button indicator	✓
Power-on self-test	✓	Power button indicator	Kensington
Camera		Power button indicator	✓
Camera resolution	✓	Operating temperature	
Camera resolution (megapixels)	1 MP	Operating temperature	0 - 40 °C
Camera resolution (pixels)	1280 x 720 pixels	Operating temperature (T-T)	-40 - 65 °C
Camera resolution (fps)	30 fps	Humidity (H-H)	10 - 90%
Network		Humidity (H-H)	0 - 95%
Network	✓	Altitude	-15,2 - 3048 m
Wi-Fi	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Altitude	-15,2 - 10668 m
LAN	✓	EPEAT Silver, Recycled	
LAN speed	10,100,1000 Mbit/s	Weight	
Bluetooth	✓	Weight	381,4 mm
Bluetooth version	4.0	Weight	267,5 mm
Ports		Weight	25,6 mm
USB 2.0	2	Weight *	2,38 kg
USB 3.2	1 (3.1 1) *	AC power	
LAN (RJ-45)	1	AC power	✓
DVI	✗	Power button	✓
VGA (D-Sub)	1	Power button	✓
S/PDIF	✗	Power button	✓
Audio	✗	Memory	
Audio	✓	3GB	✗
Audio	✗	Maximum internal memory (64-bit)	8 GB
Audio	✗	Intel®	VT-d, VT-x
Audio	✗	Intel®	VT-d, VT-x
Audio	✗	Operating temperature	
Audio	✗	Operating temperature	0 - 40 °C
Audio	✗	Operating temperature	-40 - 65 °C
Audio	✗	Humidity	10 - 90%
Audio	✗	Humidity	0 - 95%
Audio	✗	Altitude	-15,2 - 3048 m
Audio	✗	Altitude	-15,2 - 10668 m
Software		Weight	
Software	✓	Weight	381,4 mm
Software	✓	Weight	267,5 mm
Software	✓	Weight	25,6 mm
Software	✓	Weight *	2,38 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.