


ASUS H110M-E/M.2 Intel® H110 LGA 1151 (Socket H4) micro ATX

Brand : ASUS

Product code: 90MB0RK0-M0AAY0

Product name : H110M-E/M.2



ASUS H110M-E/M.2. **Processor:** Intel, **Socket:** LGA 1151 (Socket H4), **Memory:** Intel® Celeron®, Intel® Pentium®. **Memory Type:** DDR4-SDRAM, **Memory Capacity:** 32 GB, **Memory Configuration:** DIMM. **Storage:** SATA III. **Display:** 1024 MB, **Resolution:** 4096 x 2160 pixels. **Network:** LAN **Chipset:** Realtek RTL8111H

Processor		I/O	
Processor	Intel	HDMI	1
Socket	LGA 1151 (Socket H4)	USB	1
Processor Family	Intel® Celeron®, Intel® Pentium®	DisplayPort	✓
Memory		Storage	
Memory Type	DDR4-SDRAM	LAN	✓
Memory Capacity	2	Storage Controller	Realtek RTL8111H
Memory Configuration	DIMM	LAN Chipset	Realtek RTL8111H
ECC	Non-ECC	Operating System	
Memory Frequency	2133 MHz	Operating System	Intel® H110
Memory Capacity	32 GB	Audio	Realtek ALC887
Memory Configuration	✓	Audio Channels	7.1 channels
Storage		Form Factor	PC
Storage Type	SATA III	Form Factor	micro ATX
Storage Capacity		Processor	Intel
Display		Form Factor	ATX
Display Type	1024 MB	Operating System	Windows 10 Education x64, Windows 10 Enterprise x64, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8.1 Enterprise x64, Windows 8.1 Pro x64, Windows 8.1 x64
Display Resolution	4096 x 2160 pixels	Operating System	
Display Configuration	2		
I/O			
USB 2.0	1		
USB 3.2 Gen 1 (3.1 Gen 1)	1		
SATA III	4		
SATA	4		
S/PDIF	✓		
Audio	✓		

標準 I/O		標準 I/O	
ATX 電源コネクタ (24-ピン)	✓	PCI 拡張スロット x1 (Gen 2.x) コネクタ	2
EATX 電源コネクタ (24-ピン)	1	PCI 拡張スロット x 16 (Gen 3.x) コネクタ	1
CPU 冷却ファン	✓	M.2 (M) コネクタ	1
標準 25pin 平行ポート	1	BIOS	
COM 標準 25pin 平行ポート	1	BOIS コネクタ *	UEFI AMI
標準 I/O		BIOS コネクタ	16 Mbit
USB 2.0 コネクタ *	4	ACPI コネクタ	5.0
USB 3.2 コネクタ 1 (3.1 コネクタ 1) コネクタ-A コネクタ *	2	標準 CMOS コネクタ	✓
標準 LAN (RJ-45) コネクタ *	1	標準 I/O	
PS/2 コネクタ	2	Intel® コネクタ コネクタ コネクタ	2.0
VGA (D-Sub) コネクタ *	1	標準 I/O コネクタ コネクタ コネクタ (コネクタ)	✓
		標準 I/O	
		標準 I/O	226 mm
		標準 I/O	185 mm
		標準 I/O	
		標準 I/O	SATA
		標準 I/O	✓
		標準 I/O	✓

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.