

Fujitsu PRIMERGY TX1330 M3 servrar 0 GB Tower Intel® Xeon® E3-1230V6 3,5 GHz 16 GB DDR4-SDRAM

Märke : Fujitsu

Produktfamilj: PRIMERGY

Produktkod:
VFY:T1333SX100DE/5

Product name : TX1330 M3

Fujitsu PRIMERGY TX1330 M3. Processorfamilj: Intel® Xeon®, Processorfrekvens: 3,5 GHz, Processor: E3-1230V6. Internminne: 16 GB, Typ av internminne: DDR4-SDRAM, Minneslayout: 1 x 16 GB. Total lagringskapacitet: 0 GB. Nätverksansluten (Ethernet), Kabelteknik: 10/100/1000Base-T(X). Optisk enhetstyp: DVD Super Multi. Chassityp: Tower

Processor		Anslutningar	
Processortillverkare *	Intel	Antal USB 3.2 Gen 1 (3.1 Gen 1) typ A-portar	5
Processorfamilj *	Intel® Xeon®	Kvalitet på VGA (D-Sub) porten	1
Processor *	E3-1230V6	Seriella portar	1
Processorfrekvens *	3,5 GHz	Expansionsplatser	
Processorboostfrekvens	3,9 GHz	PCI Express x4 (Gen 3.x)-kortplatser	2
Processorkärnor	4	PCI Express x8 (Gen 3.x)-kortplatser	2
Processorns cache	8 MB	Design	
Moderkortets chipset	Intel® C236	Chassityp *	Tower
Minneskanaler som stöds av processorn	Dual	Prestanda	
Antal processorer installerade	1	Trusted Platform Module (TPM)	✓
Värmeavledningseffekt (TDP)	72 W	Programvara	
Processorns cachetyp	Smart Cache	Installerat operativsystem *	✗
Systembuss, hastighet	8 GT/s	Kompatibla operativsystem *	Microsoft Hyper-V Server 2016
Max antal processorer	1		Microsoft Windows Server 2016
Kompatibla processorer	Intel® Xeon®		Datacenter Microsoft Windows Server 2016 Standard Microsoft
Processorsockel	LGA 1151 (uttag H4)		Windows Server 2016 Essentials
Processorlitografi	14 nm		Microsoft Windows Storage Server 2016 Standard Microsoft Hyper-V
Processortrådar	8		Server 2012 R2 Microsoft Windows Server 2012 R2 Datacenter
Processorns driftlägen	64-bit		Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2 Essentials Microsoft
Högsta internminne som stöds av processorn	64 GB		Windows Server 2012 R2 Foundation Microsoft Windows Storage Server 2012 R2 Standard Microsoft Hyper-V Server 2012
Minnestyper som stöds av processorn	DDR3L, DDR4-SDRAM		Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2012 Essentials Microsoft Windows Server 2012
Minnesklockfrekvens som stöds av processorn	1866,2400 MHz		Foundation VMware vSphere 6.5 VMware vSphere 6.0 SUSE Linux Enterprise Server 12 Red Hat Enterprise Linux 7 Univention Corporate Server 4
Minnesbandbredd som stöds av processorn (max)	37,5 GB/s	Processor specialfunktioner	
Processor med ECC-stöd	✓	CPU konfiguration (max)	1
Execute Disable Bit-säkerhet	✓	Förstärkt Intel Speedstep Technology	✓
Idle stater	✓	Intel® Virtualization Technology for Directed I/O (VT-d)	✓
Termiska övervakningsteknik	✓	Intel® Hyper Threading Technology (Intel® HT Technology)	✓
Högsta antal PCI Express-platser	16	Intel® Turbo Boost Technology	2.0
Stödda instruktionsset	AVX 2.0, SSE4.1, SSE4.2		
Inbäddade alternativ	✗		
Etisk processor (Conflict Free)	✓		
Intelligent Platform Management Interface (IPMI) stöd	✓		
Minne			
Internminne *	16 GB		
Typ av internminne *	DDR4-SDRAM		
Minnesplatser	4		
ECC	✓		
Minne klockhastighet	2400 MHz		

Minne		Processor specialfunktioner	
Minneslayout	1 x 16 GB	Intel® Quick Sync Video Technology	✗
Maximalt internminne *	64 GB	Intel® InTru™ 3D-teknik	✗
Lagringsmedia		Intel® Clear Video HD Technology (Intel® CVT HD)	✗
Total lagringskapacitet *	0 GB	Intel® Smart Cache	✓
Hårddiskkapacitet	0 GB	Intel® AES nya instruktioner (Intel® AES-NI)	✓
Antalet hårddiskar som stöds	8	Intel® Trusted Execution Technology	✓
Hårddiskstorlek som stöds	2.5"	Intel® VT-x med utökad Sida Tabeller (EPT)	✓
RAID-stöd *	✓	Intel® Secure Key	✓
Stöd för hot-plug	✓	Intel® TSX-NI	✓
Optisk enhetstyp *	DVD Super Multi	Intel® OS Guard	✓
Lagringsenhetsgränssnitt som stöds	SAS, Serial ATA III	Intel Clear Video Technology	✗
Grafiken		Intel Software Guard Extensions (Intel SGX)	✓
Ombord grafikkort	✗	Intel® 64	✓
Nätverk		Intel Virtualization Technology (VT-x)	✓
LAN-styrenhet	Intel I210	Intel HD Graphics	✗
Nätverksansluten (Ethernet)	✓	Miljökrav	
Kabelteknik	10/100/1000Base-T(X)	Temperatur vid drift	5 - 40 ° C
Typ av ethernet-gränssnitt	Gigabit Ethernet	Intervall för relativ operativ luftfuktighet	10 - 85%
Anslutningar		Vikt & dimension	
Antal LAN (RJ-45) anslutningar *	3	Bredd	177 mm
Antal USB 2.0 anslutningar	5	Djup	560 mm
		Höjd	455 mm
		Övrigt	
		iSCSI-stöd	✓

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.